

NISSAN 20W-50 SN

Material Code:

Nissan Genuine Motor Oil SAE 20W50 API SN is a high-quality engine oil specially designed for Nissan vehicles. It has been created after extensive research and on-field testing around the world.

Nissan Genuine Motor Oil SAE 20W50 API SN is uniquely designed to enhance levels of performance, lubrication and engine protection.

Nissan Genuine Motor Oil SAE 20W50 API SN is an advanced gasoline engine oil, which meets the stringent manufacturer engine oil with latest specification.

❖ SPECIAL FEATURES

1. Good thermo-oxidative stability minimises deposits & sludge build-up and reduces oil thickening, thereby facilitating extended oil life and active cleaning agents ensure engine cleanliness.
2. Excellent anti-wear, which minimises engine wear and thereby reduce maintenance cost.
3. Superior dispersants provide excellent control over soot induced to prevent oil thickening.
4. Excellent engine performance even under the most severe operating conditions.
5. Superior viscosity retention ensures protection at all operating temperatures.

❖ PACK SIZE

1L, 4L, 208L

❖ PERFORMANCE LEVEL

API SN

❖ APPLICATIONS

- Approved for Nissan Vehicles & recommended for other gasoline engines.

❖ TYPICAL PROPERTIES

SAE Viscosity Grade Quality Grade	20W-50 SL
Appearance	Clear
Density (15°C), g/cm ³	0.8717
Flash Point (COC), °C	258
Kinematic Viscosity (100°C), mm ² /s	17.46
Viscosity Index	132
Pour Point, °C	-33
TBN (HCL), mg KOH/g	7.40

Note: The Typical Properties may be changed without notice



Handling Precautions

▼ Follow these precautions when handling this product.

Classification of the substance or preparation :	Not a dangerous preparation according to 1999/45/EC.
Most important adverse :	No adverse hazards.
Most important adverse human health effects :	None under normal conditions.
Precautionary Statements : Prevention	No naked lights. No smoking. Keep away from sources of ignition. Handle in accordance with good industrial hygiene and safety procedures.
Response	After inhalation : Assure fresh air breathing. Obtain medical attention if breathing difficulty persists. After contact with skin : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Seek medical attention if irritation develops. After contact with eyes : Rinse immediately with plenty of water. Seek medical attention if irritation develops. After ingestion : DO NOT INDUCE VOMITING. Seek medical attention immediately. Other Information : If there is any suspicion of aspiration into the lungs either directly or as a result of vomiting, obtain medical advice.
Storage	Keep container closed when not in use. Keep at temperature not exceeding 45°C. Keep only in the original container in a cool, well ventilated place.
Disposal	Waste disposal : Dispose in a safe manner in accordance with local/national regulations. Waste-disposal procedures : See Directive 2001/118/EC Industrial waste number (EURAL) : 13 02 05 - mineral-based non-chlorinated engine, gear and lubricating oils. Contaminated packaging : Do not attempt to refill or clean containers without proper instructions. Do not cut , pressurise, weld, braze, solder, drill, grind or expose such containers to the heat, flame, sparks, static electricity or other sources of ignition. They may explode and cause injury or death.